



RIBBON LIGHTING & LOW PROFILE SURFACE EXTRUSION

Code	Description
S-RIB 5M 14W-WW/CW	60W LED RIBBON LIGHT COOL/WARM WHITE
S-RIB 5M 5W-WW/CW	24W LED RIBBON LIGHT COOL/WARM WHITE
S-RIB 5M 5W RGB	24W RGB LED RIBBON LIGHT
SRIB2MST	LOW PROFILE SURFACE EXTRUSION PROFILE

RIBBON LIGHT FEATURES:

- 3 Yr. Guarantee
- IP Rating: IP65
- Complete with LED Driver
- IP65 14.5W 5M C/W 60W Driver
- IP65 24W 5M C/W 30W Driver
- 5M Length
- Voltage 12V
- Beam Angle 120°
- Available In Cool / Warm White



Remote Control supplied with S-RIB 5M 5W RGB



SRIB2MST

Low Profile Surface Extrusion Profile with push on PC diffuser

- 2 metre Extrusion Strip
- Complete with 2 end caps, mounting clips and screws
- Size: 2Mt Length x 8.8mm depth x 14.4mm width
- Compatible with the S-RIB ribbon light range




End Cap



Mounting Clip



Screw



Solas Geal Distribution Ltd, Unit 7 & 8 Ashbourne Business Centre, Ballybin Road, Ashbourne, Co. Meath, A84 YP58, Ireland.
SGD Solas Geal UK Ltd, Unit 32 Junction One Business Park, Valley Road, Birkenhead, Wirral, Merseyside, UK, CH41 7ED.

Tel: +353 1 8357447. UK Ph: 0330 551 7000. Fax: 00353 1 8357448. Email: info@sgd.ie. Website: www.sgd.ie